

# P920C 8,5 kW

## Multi Comfort Pellet Stove



Double motor, double comfort

Thanks to the Multicomfort Plus system, stoves equipped with the double Multifuoco Dual Power motor allow for separately managing the two motors **to heat multiple rooms with different temperatures**, set according to personal needs.



Remote management

Modern **pellet stoves can be also be programmed and managed remotely**. When the user is away from home, the ignition and switch-off times can be set through Wi-Fi via the My Piazzetta app. At home, the stove can instead be operated also via Bluetooth, using a smartphone.



S.C. Woodwise S.R.L.

CUI: 49611635; EUID: ROONRC. J25/99/2024

Gheroghe Sincai, 37D - 220027 Drobeta Turnu Severin - Romania | office@woodwise.ro | +(40) 0771175897

## GENERAL FEATURES

- Heating: Multifuoco System® with 3 power levels and manual or automatic control. Hot ductable air
- Natural Mode: yes
- Power levels: 4
- Radiant Majolica: yes
- Cladding / Top: majolica / steel - cast iron
- Front ventilation: adjustable vent
- Humidifier: stainless steel
- Remote control with LCD display:
- Multicomfort: standard
- Multicomfort Plus: standard
- Ambient probe for temperature control: as standard feature
- Control panel with digital controls: yes
- Module WiFi - Bluetooth for MyPiazzetta App: standard
- Wireless probe for temperature management: optional
- Timer-controlled thermostat with programming: 6 daily time frames
- Eco / Energy Saving function: yes / yes
- Glass cleaning: continuous air flow
- Cyclic brazier cleaning: yes
- Ash vacuum cleaner: as standard feature
- Installation: flush with the wall - corner
- Standard flue outlet position: LH rear
- One-piece firebox: airtight in steel
- Firebox: cast iron
- Door / Handle: cast iron with ceramic glass resistant up to 750°C / detachable
- Combustion air kit:
- Design door:
- Air Combustion System Function: yes
- Pellet Quality System Function: yes
- Ash conveyor: steel
- Side ventilation: optional vent, fixed
- Combustion air kit:

## TECHNICAL DETAILS

- Rated thermal power (min - max) kW 3,3 - 8,5
- Efficiency (min - max) % 91,2 - 91,2
- Energy efficiency class A+
- Rated consumption (min - max) kg/h 0,75 - 1,95
- Tank capacity kg 18
- Weight kg 147
- Standard flue outlet Ø cm 8
- Model P920 C

## COVERS

