



Double motor, double comfort

Thanks to the Multicomfort Plus system, stoves equipped with the double Multifuoco Dual Power motor allow for separately managing the two motors to heat multiple rooms with different temperatures, set according to personal needs.



Remote management

Modern pellet stoves can be also be programmed and managed remotely. When the user is away from home, the ignition and switch-off times can be set through Wi-Fi via the My Piazzetta app. At home, the stove can instead be operated also via Blutooth, using a smartphone.

## P230T 11 kW



## GENERAL FEATURES

- \*Heating: Multifuoco System® with 4 power levels and manual or automatic control. Hot ductable air
- ·Natural Mode: yes
- Power levels: 5
- Radiant Majolica: yes
- \*Dual Power System: 4 power levels and manual or automatic control
- \*Cladding / Top: majolica / majolica
- •Rolling Top: sliding top
- \*Front ventilation: adjustable vent
- ·Humidifier: stainless steel
- Remote control with LCD display:
- ·Multicomfort: standard
- ·Multicomfort Plus: standard
- ·Ambient probe for temperature control: as standard feature
- Control panel with digital controls: yes
- \*Module WiFi Bluetooth for MyPiazzetta App: standard
- ·Wireless probe for temperature management: standard
- \*Timer-controlled thermostat with programming: 6 daily time frames
- \*Eco / Energy Saving function: yes / yes
- ·Glass cleaning: continuous air flow
- Cyclic brazier cleaning: yes
- Ash vacuum cleaner: as standard feature
- Installation: flush with the wall corner
- Standard flue outlet position: LH rear
- One-piece firebox: airtight in steel
- \*Firebox: cast iron
- \*Door / Handle: cast iron with ceramic glass resistant up to 750°C / detachable
- \*Combustion air kit:
- Design door: steel with screen-printed tempered glass
- Air Combustion System Function: yes
- Pellet Quality System Function: yes
- \*Ash conveyor: steel
- ·Side ventilation: optional vent, fixed
- \*Combustion air kit:

## **TECHNICAL DETAILS**

- \*Rated thermal power (min max) kW 3,9 11,0
- \*Efficiency (min max) % 89,7 91,8
- \*Energy efficiency class A+
- \*Rated consumption (min max) kg/h 0,90 2,48
- Tank capacity kg 26
- ·Weight kg 186
- \*Standard flue outlet Ø cm 8
- •Model P230 T

## COVERS

















